

**AULICK**

**AU** *limate*



**Trailer Lengths Available from 42' to 53' OAL**

**Belt widths are 54 inch**

**Side heights 60 inch or 70 inch , side extensions available**

**Belt and rear gates are all powered by one simple hydraulic system**

**Full height plastic 3/16 HMW side liner full length , 3/8 UHMW under chain**

**Tandem air ride is standard ,24 inch king pin, other axle configurations available**

**Roll Tarp –Air ride suspension – 11.5 x 22.5 radials on 10 bolt hub pilot wheels**

**Standard – Durable-and Repairable All steel Construction**

**Aulick Industries 1-877-285-4258 (specifications subject to change)**



**SPECIFICATIONS : 54 inch belt  
Tandem axle**

<b>Model</b>	<b>length</b>	<b>capacity</b>	<b>belt width</b>	<b>height</b>	<b>aprox weight</b>
<b>4260542</b>	<b>42 ft</b>	<b>56 cu/yd</b>	<b>54</b>	<b>9ft 8in</b>	<b>15260</b>
<b>4270542</b>	<b>42ft</b>	<b>66 cu/yd</b>	<b>54</b>	<b>10ft 6in</b>	<b>16080</b>
<b>4660542</b>	<b>46ft</b>	<b>61 cu/yd</b>	<b>54</b>	<b>9ft 8in</b>	<b>15920</b>
<b>4670542</b>	<b>46 ft</b>	<b>73 cu/yd</b>	<b>54</b>	<b>10ft 6 in</b>	<b>16880</b>
<b>4860542</b>	<b>48ft</b>	<b>65 cu/yd</b>	<b>54</b>	<b>9ft 8in</b>	<b>16600</b>
<b>4870542</b>	<b>48 ft</b>	<b>76 cu/yd</b>	<b>54</b>	<b>10ft 6in</b>	<b>16950</b>

**Aulick Industries 1-877-285-4258**

**Capacity's/weights are approximate and subject to change**



**SPECIFICATIONS : 54 inch belt**  
**Triple axle**

<b>Model</b>	<b>length</b>	<b>capacity</b>	<b>belt width</b>	<b>height</b>	<b>aprox weight</b>
<b>4660543</b>	<b>46ft</b>	<b>61 cu/yd</b>	<b>54</b>	<b>9ft 8 in</b>	<b>17500</b>
<b>4670543</b>	<b>46ft</b>	<b>69 cu/yd</b>	<b>54</b>	<b>10ft 8 in</b>	<b>17900</b>
<b>4860543</b>	<b>48ft</b>	<b>65 cu/yd</b>	<b>54</b>	<b>9ft 8in</b>	<b>18100</b>
<b>4870543</b>	<b>48 ft</b>	<b>76 cu/yd</b>	<b>54</b>	<b>10ft 6in</b>	<b>18700</b>

**Aulick Industries 1-877-285-4258**

**Capacity's/weights are approximate and subject to change**

# **AU** *ltime*



**Solid side extensions  
(optional)**



**Full open – unrestricted  
end gate ( standard)**



**Grain Chute (optional)**



**Tapered extensions (optional)**

**Aulick Industries 1-877-285-4258**

# AU *ultimate*



**Electric valve (optional)**



**Aluminum Sheeting (optional)**



**Grain chute (optional)**



**Aulick Industries 1-877-285-4258**

# AU *l*timate



**Tandem set forward 18 inches**



**Tandem with air lift tag (or pusher)**



**Spread axle**



**10-2 triple**

**Aulick Industries 1-877-285-4258**



# Standard Specifications

**Floor Chain is 88c Pintle Chain , 2 Strands**

**Easy Access belt adjustment at front of trailer**

**2 Ply belt flaps full width of floor 17 ½ x 54 inch**

**Bolt on (removable) 5<sup>th</sup> wheel**

**Gear – Drive is a Eskridge 130000 in/lb torque 18000 lb radial load**

**2 15/16 rear diameter drive shaft , with weld on sprockets and splined hub**

**Hydraulic Top Hinge Main Gate , 41 inches above the top of the trailer when open**

**Plastic HMW side liner 3/16 thick , one piece full length from floor to top of trailer , both sides**

**Plastic UHMW floor liner 3/8 thick , full width of belt, full length , one piece**

**Extended rear discharge with wings**

**Mechanical latch on rear gate , for positive lock**

**High Pressure in-line hydraulic oil filter**

**50000 LB landing gear**

**ABS brake system , 2S/1M anti/lock brake system**

**Front and Rear Fenders**

**11 x 22.5 Radial tires on 10 bolt rims , centrifuge brake drums**

**22500 Lb axles with 16.5 x 7 brakes s-cam with park brake chambers on 2 axles**

**Trailer is painted with 2 part primer and 2 part top coat**

**DOT Lighting and reflective tape**

**(specifications subject to change)**