



**Specifications:**

LENGTH:	32 FT. TO 42 FT.
CAPACITY:	20 CUBIC YARDS WATER LEVEL 23.5 CUBIC YARDS WITH 10" BANG BOARDS
GATES:	ASTM A-36 STEEL WITH ADJUSTABLE SLIDE-LOCKS. GATES ARE AIR CONTROLLED, ELECTRIC CONTROLLED FROM THE CAB OF THE TRUCK AND MANUALLY FROM THE GROUND.
LOWER HOPPER:	54" X 108" - SINGLE HOPPER WITH 3/16" PLATE WITH 1/4" SIDE WALLS. ASTM A-36
UPPER HOPPER:	COMPLETE UPPER HOPPER CONSTRUCTED FROM 10 GAUGE, CQA-569
AIR SYSTEM:	TWO 8" BORE AIR CYLINDERS WITH WATER TRAP AND OILER FOR LUBRICATION. QUICK RELEASE VALVES. ONE 60 GALLON AIR RESERVOIR TANK.
FIFTH WHEEL:	OSCILLATING FIFTH WHEEL PLATE WITH AN 18 INCH KING PIN SETTING
RIMS:	EIGHT (8) 8.25 X 24.5 STEEL 10 HOLE DISC
TIRES:	EIGHT (8) 11R X 24.5 DUNLOP SP-160 RADIALS
AXLES:	TWO (2) ROCKWELL 25,000 LB. 5" TUBULAR, 5/8" WALL WITH 16 1/2" X 7" BRAKES AND 30 X 30 BRAKE CHAMBERS MOUNTED ON TOP OF AXLES, WITH WINDROW DEFLECTORS
SUSPENSION:	HUTCH H-9700 48,000 LB. SUSPENSION
ABS BRAKES:	ABS BRAKES 2S1M ON ONE AXLE ONLY
FENDERS:	FRONT AND REAR
LIGHTS:	ICC AND DOT APPROVED GROTE BLUE SEAL LIGHTING SYSTEM
LANDING GEAR:	DROP LEG 4" X 4" SQUARE TUBE, MOUNTED ON FRONT OF DOORS
PAINT:	CARBOLINE PRIMER AND CARBOLINE WHITE PAINT
REAR BUMPER:	PUSH BLOCK WITH DOT APPROVED UNDER RIDE BUMPER
TOP RAIL:	4" X 6" X 3/16" TUBE, ASTM A-36
BOTTOM RAIL:	4" X 6" X 3/16" TUBE, HIGH TENSILE 80,000 PSI
SIDES:	54" HIGH, CORRUGATED SIDES WITH DOUBLE WALL CONSTRUCTION