

40' TANDEM AXLE TRAILER - LEAF SPRING
- MODEL #SS402-4LS -

40 ft. 20" Deep I-Beam Frame
34 ft. FlexCorner, Leak Proof, Balanced Tub
24.2 Cubic Yards Struck
Quick Left to Right Dump Change
Low Center of Gravity Design
Large Tub Side Stiffener, Maintains 102" when Loaded
Low Cut Center Divider
Two Year Warranty on Manufactured Parts
6 Tub Pivots with No-Grease Bushings, Reduced Dump Twist
20 Second Dump (30 second Cycle) at 33 GPM Flow
Replaceable, Certified UnderRide Bumper Protection
Bolt-on Rear Push / Lift Block
Rubber Edge Fenders with Enclosed LED Lighting

FRAME AND SUSPENSION

Frame- 20" Waffled Tandem Hutch Suspension

HUB PILOT AXLES- RATING, TRACK, HUB & DRUM TYPE - ONE AXLE ABS READY
25,000# Meritor 77.5" Track Oil Bath Hubs

HALDEX ABS BRAKES

ABS- 1 Axle 2S1M System

RUBBER FENDER AND LED LIGHT KIT

Rubber Fender Kit Front and Rear with LED Light Package

PRINCE HYDRAULICS

Standard Hydraulic Package Tandem
Trailer Mounted Electric over Hydraulic Valve (In Cab Switch Box)

DROP BOTTOM TUB ASSEMBLY

Tub-34' 1/4" (6mm) FLX-500
Tub-34' 1/4" (6mm) AR400F

CYLINDER SIZE

6" Diameter (Dump 62,000# Payload @2250 psi)
5" Diameter (Dump 43,000# Payload @2250 psi)

PUSHBLOCK & UNDERRIDE (Optional Selection)

Extended Pushblock and UnderRide Bumper- Bolted on
No Bumper - Leave Blank - Bumper can be purchased and installed at later date.

LEAD TRAILER ATTACHMENT (Optional)- includes through Hydraulics, Air,

Electrical and Pintle Hitch
Lead Trailer Kit for 40ft. Chassis

HIGH QUALITY DUAL WHEELS & TIRES

Include: Dunlop SP160, GoodYear G314, Firestone FT455, Kelly K TSA, Hankook F80
-OR- equivalent - manufacturer's choice. (Premium Quality Tires: Michelin -OR- equivalent)
11R22.5 on White Steel Wheels
11R22.5 on Machine Finished Aluminum Wheels
11R24.5 on White Steel Wheels
11R24.5 on Machine Finished Aluminum Wheels

HIGH QUALITY SUPER SINGLE WHEELS & TIRES

Include: Dunlop SP160, GoodYear G314, Firestone FT455, Kelly KRM -OR-
equivalent - manufacturer's choice. (Premium Quality Tires: Michelin -OR- equivalent)
385/65R22.5 Super Single on Machine Finished Aluminum Wheels
425/65R22.5 Super Single on Machine Finished Aluminum Wheels

TARP (Optional Selection) Adds Approx. 300lbs

Factory Installed Roll-Rite Electric Tarp for a 34' Tub Mesh
Factory Installed Roll-Rite Electric Tarp for a 34' Tub Solid