



Delivering The Difference

Model 135/150



LANDOLL 135/150

Fixed Gooseneck Beavertail

Standard & Optional Equipment/Features—Model 135/150 Fixed Gooseneck Beavertail

S=Standard O=Optional

Model 150	50 Ton	100,000#		
Model 135	35 Ton	70,000#		
MAINFRAME				
- Fabricated 80,000 # PSI			S	S
- Four Beam Design			S	S
- Capacity—70,000# Distributed / 50,000# Concentrated in 10'			S	
- Capacity—100,000# Distributed / 70,000# Concentrated in 10'				S
KINGPIN SETTING				
- 18" Setting			S	S
- 86" Swing Clearance			S	S
CROSSMEMBERS				
- 4" Jr. I-Beam on 12" Centers			S	S
DECK & FEATURES				
- 102" Wide			S	S
- Lower Deck Length				
135—23'7", 26'7", 28'7", 31'7"			S	S
150—28'7", 31"7"			S	S
- 90 Degree Slope Drop			S	S
- 37¼" Deck Height (Loaded)			S	S
- 1¾" Nominal Apitong (Lower Deck)			S	S
- 20" Loaded Ground Clearance			S	S
UPPER DECK WINCH OPTIONS:				
- 12,000 lb. Worm Gear			O	O
- 15,000 lb. Planetary Winch			O	O
- 20,000 lb. Worm Gear Winch			O	O
- Remote Control Single Function—Street & Curb Rear			O	O
- Cable Roller Guide for Winch—12,000 lb., 15,000 lb. Or 20,000 lb. Slope or Upper Deck			O	O
TIE DOWNS/CHAIN GOTCHAS				
- Double Key Hole Chain Slots on 24" centers			S	S
- "D" Ring Bolt on at Winch (each) (Two Locations Available)			O	O
- Flush Mounted "D" Rings (each)			O	O
TOOLBOX				
- Storage Area Upper Deck 23"x 35"x 8" without lid			S	S
DECK ACCESSORIES				
- Lower Deck Lockable Tool Box (Curb Side or Street Side) (42" wide x 28" deep x 9" high)			O	O
- Lockable Lid for Storage Area			O	O
- 96" Width Not Available				
SLOPE RAMP				
- 5 Ft. Aluminum Ramps (Portable) 8,000 lb. Capacity Each			O	O
- Upper Deck Ramp (Air Operated)			O	O
- Landoll Traction Ramps (Steel)			O	O
BULKHEADS				
- 16"/24" 2-Position Bulkhead/Front Extension (Solid)			O	O
- 48" High Mesh 102" or 96" Wide			O	O
- Bolt on Binder Storage Rack for 48" Bulkheads			O	O
- Halogen Work Light-Dual (Mounted on Bulkheads)			O	O
- Spare Tire Carrier 48" Bulkhead Front Mounted			O	O
- Spare Tire Carrier 48" Bulkhead Rear Mounted			O	O
- Dual Spare Tire Carrier 48" Bulkhead, Front Mounted			O	O
PARKING STANDS				
- Pin Drop (in lieu of standard)			O	O
AXLES				
- (2) 25,000 Tandem Dual Tire, Oil Bath Bearings			S	
- (3) 25,000 Tandem Dual Tire, Oil Bath Bearings				S
SUSPENSION				
- Multi-Leaf Springs 45,000 capacity			S	
- Multi-Leaf Springs 67,200 capacity H9700/60" Spread				S
- Neway Air Ride RLU228 22,500# Capacity with Manual			O	O

Specifications subject to change without notice or obligation.

Model 150	50 Ton	100,000#		
Model 135	35 Ton	70,000#		
BRAKES				
- Automatic Slack Adjusters			S	S
- 12.25 x 7.5 Full Air w/spring Brakes One Axle				
- ABS, Rockwell 4S2M			S	S
OIL SEAL HUBS				
- Internal Mated Assembly			S	S
TIRES/WHEELS				
- 10R 17.5 Goodyear LRH			S	S
- Hub Pilot/Steel Outboard Brake Drum			S	S
RIMS				
- 17.5 x 6.75 Tubeless			S	S
- 17.5 Aluminum wheels (8 Bolt Polished)			O	O
TIRES & RIMS				
- Spare Goodyear Tire & Hub Pilot Type Rim (21570R 17.5)			O	O
- Spare Goodyear Tire & Hub Pilot Type Rim (10R 17.5)			O	O
- 10R 17.5 Michelin in Lieu of Standard Goodyear			O	O
- Spare Michelin Tire & Hub Pilot Type Rim (10R 17.5)			O	O
- 235/75R 17.5 Bridgestone Tires in Lieu of Standard Goodyear			O	O
- Spare Bridgestone Tire & Hub Pilot Type Rim (235/75R 17.5)			O	O
- 215/70R 17.5 Michelin Tires in Lieu of Standard Goodyear			O	O
- Spare Michelin Tire & Hub Pilot Type Rim (215/70R 17.5)			O	O
- Hubmeter			O	O
- 255/70R 22.5 Goodyear Tires in Lieu of Standard Goodyear			O	O
HYDRAULIC POWER SOURCE				
- Air Shift PTO & Wet Kit for Tractor—Not Installed (30 Gallon Tank Required)			O	O
- Installation of PTO & Wet Kit (Control)			O	O
- Hydraulic Quick Couplers 1 Male/1 Female (Matches Trailer) (Part # 105902)			O	O
HYDRAULIC HOOK UP				
- Hydraulic Quick Couplers 2500 PSI/17 GPM			O	O
AIR/ELECTRICAL CONNECTION				
- 7 Way Receptacle (Electrical)			S	S
LIGHTS				
- Light Tail System, Sealed Beam Grommet Mounted with Sealed Wiring Harness, Center Mounted Turn Signal			S	S
FINISH/COLOR				
- Steel Grit Shot Blast to Bright Metal			S	S
- Epoxy Primer			S	S
- Acrylic Urethane White, Black, Yellow, Blue, Red, Green			S	S
WEIGHT				
- 135-40 12,000			S	
- 150-48 14,500				S
BEAVERTAIL				
- 68" Self-Cleaning Beavertail			S	S
- Apitong Wood Covered Beavertail			O	O
- Traction Bars for Wood Covered Beavertail			O	O
RAMPS				
- 5' Self-Cleaning Adjustable Spring Assisted Flipover			S	S
- Heavy Duty Crawler Ramp (Wood Filled)			O	O
- Third Ramp—Self-Cleaning or Wood Filled			O	O

