



Delivering The Difference

Model 950



LANDOLL 950



Traveling Tail

Standard & Optional Equipment / Features - Model 950 Traveling Tail

S=Standard O=Optional

MODEL 950 50 Ton 100,000#	
MAIN FRAME - Fabricated 80,000 #/100,000# PSI - Four Beam Design - Capacity-100,000# Distributed /70,000# Concentrated in 10'	S S S
KINGPIN SETTING - 18" Setting - 86" Swing Clearance	S S
CROSSMEMBERS - 4" Jr. I-Beam on 8" Centers	S
DECK & FEATURES - 102" Wide - 90 Degree Slope Drop - 37-1/4" Deck Height (Loaded) - 1 3/8" Nominal Apitong/Landoll Traction Plate - 20" Loaded Ground Clearance	S S S S S
TAIL - 12 Ft. (15° Load Angle) Model 950-45-12 (Lower Deck Length 34') Model 950-48-12 (Lower Deck Length 37') - 15 Ft. (11° Load Angle) Model 950-48-15 (Lower Deck Length 37') Model 950-51-15 (Lower Deck Length 40') - Flush Double Key Hole Side Chain Slots (For Tie Downs on Tail) - Flat Approach Plate w/Six Gotcha Tie Downs at Rear of Plate - Apitong Wood Covered - Lifting Capacity 24,000#	S S S S S S S S S
WINCHES & ACCESSORIES - Upper Deck 12,000# Worm Gear w/85'1/2" Cable w/Wear Plate - Slope Mtd Winch Optional - 12,000#, 15,000#, 20,000#	S O
TIE DOWNS / CHAIN GOTCHAS - Double Key Hole Chain Slots/Gotchass on 32" Centers	S
TOOL BOX - Street Side Under Lower Deck (42"W x 28"D x 9"H)	S
SLOPE RAMP - 5 Ft. Aluminum Ramps (Portable) - Upper Deck Ramp (Air Operated) - Landoll Traction Ramps (Steel) (Portable)	O O O



MODEL 950 50 Ton 100,000#	
LIFT CYLINDER - Combination Tilt/Travel Cylinder	S
AXLES - (3) 25,000# Tandem Dual Tire, Oil Bath Bearings	S
SUSPENSION - Neway Air Ride RLU228 22,500# Capacity with Manual Dump Valve	S
BRAKES - Automatic Slack Adjusters - 12.25 x 7.5 Full Air w/spring Brakes (Two Rear Axles) ABS 4S2M Center Axle Indirect	S
OIL SEAL HUBS - Internal Mated Assembly	S
TIRES/WHEELS - 10R 17.5 Goodyear LRH - Hub Pilot/Steel Outboard Brake Drum	S S
RIMS - 17.5 x 6.75 Tubeless	S
HYDRAULIC POWER SOURCE - Truck Mtd Air Shift PTO , Pump and Hyd Res - Self Contained Hyd System Under Slope Mtd	O O
HYDRAULIC HOOK UP - Hydraulic Quick Couplers 2500 PSI/17 GPM	S
AIR/ELECTRICAL CONNECTION - 7 Way Receptacle (Electrical)	S
LIGHTS - Sealed, Potted, "LED" Grommet Mounted with Sealed-Wiring Harness, Center Mounted Turn Signal	S
FINISH/COLOR - Steel Grit Shot Blast to Bright Metal - Epoxy Primer - Acrylic Urethane White, Black, Yellow, Blue, Red, Green	S S S
WEIGHT (Estimated) - 950-48-12 19,200# - 950-51-15 19,890#	S S
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. PICTURES MAY SHOW OPTIONAL EQUIPMENT.	

