



96" Deckover Dump (D8)



Lengths
14'

Standard Features

- 14,000 lb. G.V.W.R.
- 7,000 lb. x 2 G.A.W.R.
- 2 5/16" Adjustable Ball Coupler
- Safety Chains
- 1 - Drop Leg Jack (7,000 lb.)
- 2 - Posi-lube Brake Axle (7,000 lb.)
- 6 Leaf Slipper Spring Suspension
- 4 - 16" White Spoke Wheels
- 4 - 235/80R16 Radial Tires (3,520 lb.)
- Electric Breakaway Kit w/ Charger
- DOT Reflective Tape
- 1/8" Treadplate Steel Fenders
- Toolbox
- 2 - Way Gate (Barn Doors & Spread Gate)
- 80" Slide In Channel Ramps
- 4 - D-Rings
- 40° Dump Pitch
- 12VDC Hydraulic Pump
- Scissor Lift
- 12' Control Cable
- 6" Channel Tongue
- 8" I-Beam Main Frame
- 1 Iga. Fabricated Bed Frame
- 2" x 6" x 1 Iga. Tubing Outer Bed Frame
- 3" Channel Crossmembers 16" on Center
- 10ga. Steel Bed
- 96" Wide Bed
- 12ga. Steel Sides
- 19" High Fold Down Sides
- DOT Approved Flushmount Lifetime LED Lights
- Sealed Wire Harness
- Sand Blasted, Acid Washed, Powder Coated



At PJ Trailers, every trailer we build is powder coated with Sherwin-Williams™ Powder Coat. A powder coat finish is far superior to conventional paint. It is extremely durable and does not easily crack, chip, or peel as conventional paint does. Powdercoating also helps prevent rust & corrosion making it the longest lasting and most durable finish on the market.

Coupler Options

- BP 2 5/16" Adjustable (14,000 lb.) *
- Rigid mount 2-5/16 (25,000 lb.)
- GN Load-Leveling 2 5/16" Square (30,000 lb.)
- 3" Pintle Eye - Channel-mount (21,000 lb.)
- GN 2 5/16" Round (25,000 lb.)
- GN 2 5/16" Square (25,000 lb.)

Axle Options

- (2) 7,000# Electric / Spring *
- (2) 7,000# Electric / Torsion
- (2) 7,000# Elec/Hyd Disk / Spring
- (2) 7,000# Load Range G 14ply Tires Electric / Spring
- (2) 8,000# Load Range G Tires Electric/Spring
- (2) 8,000# Load Range G Tires Elec/Hyd Disk/Spring

Tail Options

- Split / Spreader Gate *

Color Options

- Black Powdercoat *
- Grey Powdercoat
- Red Powdercoat
- White Powdercoat
- Yellow Powdercoat

Other Options

- 2nd Jack
- 6" Taller GN Riser
- 9,990 G.V.W.R.
- 12"oc Crossmembers
- 1 Extra Pair of D-Rings
- Spare Tire and Mount (Bumper Pull)
- Deck on the Neck (GN Only)
- 2-speed Jacks (12,000 lb.)

Notes:

14' 6.56 cu yds

* denotes a standard feature



Also Available with
a Gooseneck Coupler