

**ZIEMAN MODEL 2725 - BEAVERTAIL, RAMP TRAILER
TAGALONG - DECK OVER WHEELS**

G.V.W.R.: 44,320 lbs. at 55 M.P.H.

PAYLOAD CAPACITY: 35,120 lbs. at 55 M.P.H. **

TRAILER WEIGHT: 9,200 lbs.

HITCH WEIGHT: 8,000 lbs. required at Maximum payload capacity. Any reduction of the payload below the maximum will reduce the required hitch weight accordingly.

OVERALL LENGTH: 34 feet 2 inches. (including ramp overhang)

OVERALL WIDTH: 102 inches.

TONGUE LENGTH: 7 feet 3 inches.

DECK LENGTH: 25 feet. (including Beavertail)

BEAVERTAIL LENGTH: 48 inches. (center part of beavertail is opened for bucket storage).

DECK WIDTH: 102 inches.

DECK HEIGHT: 36 1/2 inches (loaded).

HITCH HEIGHT: 22" to 31" adjustable in 2 1/4" steps.

CLIMB ANGLE: Ramp = 16.0 degrees (28.7%)
Beavertail = 15.2 degrees (27.1%)

RAMPS: SPRING ASSISTED Steel, 64" long x 21.5" wide. Ramp spacing is adjustable from 96 1/2" outside to outside to 51" inside to inside. Ramp surfaces are inverted angles for traction. Stabilizer legs are part of ramps. Ramps are in vertical position when transporting.

DECKING: Wood, 2" x 12" Purpleheart. Purpleheart is a dense and straight grain wood. It is a very durable and shrink resistant wood which make is much superior to that of oak.

HITCH: Alloy steel Lunette with 3" I.D. eye. Attached to a drilled plate with four 3/4" diameter grade 8 bolts and grade C locknuts.

AXLES: Two 22,500 lb. rated each. 5" O.D. x .440" wall tube with oil hubs and Stemco seals.

ZIEMAN MODEL 2725 CONT.

BRAKES: Standard: 12.25" x 7.5" S-cam straight air drum brakes on all wheels. Anti-lock brake system, 2S/1M.
Optional: Spring-applied emergency/park system. All include emergency breakaway protection.

TIRES: Eight 215/75R17.5 (H), Tubeless Radials.

WHEELS: Eight 17.5 x 6.75 DC, steel disc with 10 lugs on a 8-3/4" diameter bolt circle.

SUSPENSION: Hutch H-9700 tandem 2-leaf slipper springs with load equalizers. 44,800 lb. rating.

TONGUE JACK: Binkley Retractable, two speed crank type with 25,000 lb. rating and a 12" quick-retract leg.

TOOL BOX: 14 Ga. steel, 10" high x 15" wide x 24" long, mounted on tongue.

TIE DOWN RINGS: Four D-rings per side. 1" diameter stock.

SAFETY CHAIN: Two 1/2" High Test chains (Grade 70) with safety hooks. Crossover type.

ELECTRICAL PLUG: A.T.A. standard 7-way.

LIGHTING: **L.E.D.**, 12 volt, to D.O.T. standards.

COLOR: Zieman charcoal gray.

STRUCTURAL: Constructed of A-36 Structural Grade steel and engineered to exceed the rated capacity.
Deck Main Rails: 14" x 26 lb. I-beams
Deck Side Rails: 8" x 11.5 lb. channels
Crossmembers: 6" x 8.2 lb. channels
Tongue Rails: Continuation of the Main Rails.
Crossmembers are pierced through the Main Rails.

** Trailer capacity may be above legal limit in some jurisdiction.